



URBAN ARROW SHORTY

Specification Sheet - EN

Bosch Active Plus | 400Wh | Tektro*

SPECIFICATIONS

Frame (rear)	UA4.2, aluminium
Motor	Bosch Active Line Plus Gen 3, 250W - max. 50Nm
Battery	Bosch 400Wh
Display	Bosch Purion
Rear hub, internal gear	Enviolo Trekking, 36H
Shifter	Enviolo CT - City
Drive line	Chain, KMC X1 Silver 102L
Rear sprocket	Enviolo 17T flat
Front sprocket	Lasco 38T, 4 hole, 104BCD
Chainguard	Hebie chainglider front 38T, 350R NV16, 16-22T for Enviolo
Rear brake	Tektro Dorado HD-E730, Lever Right, 2300mm hose
Brake rotor rear	Tektro TR-180-17, 180mm 2.3mm
Adapter rear	-
Front brake	Tektro Dorado HD-E730, Lever Left, 2000mm hose
Brake rotor front	Tektro TR-180-17, 180mm 2.3mm
Adapter front	Tektro A3, IS-PM180
Brake pads	Q10RS, Red
Rear light	Spanninga Plateo XE 6V-36V
Front light	Lezyne Mini E65, 980mm cable
Front fork	UA rigid fork
Steering rod	UA Shorty steering rod & linkage
Stem	TranzX JD-ST17-2 black 1-1/8 25,4 110mm
Handlebar	Ergotec Moon cruiser 25,4 black
Grips	Ergon GC10
Pedals	C558
Seatpost	Satori Trident 31,6 400mm Black
Saddle	Selle Royal Rio Plus
Cranks	Lasco EB05 BNI 170mm
Rear rim	Ryde Andra 40 Double wall 26" x 1.75; Sapim spokes (13G)
Front rim	Ryde Andra 40 Double wall 20" x 1.75; Sapim spokes (14G)
Front hub	Shimano HB-M525A, 36H
Rear tire	Schwalbe Big Ben Plus 55-559
Front tire	Schwalbe Big Ben Plus 55-406
Valve	Schrader
Rear fender	SKS 65mm 26" Black matte
Front fender	SKS 65mm 20" Black matte
Frame colour	Black or White
Weight bike	46Kg
Outer dimensions	L 203cm x W 70cm x H 110cm
Max total weight	190Kg Bike + rider + load
Max front load	50Kg
Max rider weight	125Kg
Max rear load	25Kg

* As Urban Arrow works to continuously improve its products all specifications are subject to change. Hence, no rights can be derived from this publication. Last updated 01-03-2021



URBAN ARROW SHORTY

Specification Sheet - EN

Bosch Performance Line | 500Wh | Tektro*

SPECIFICATIONS

Frame (rear)	UA4.2, aluminium
Motor	Bosch Performance Line Gen 3, 250W - max. 65 Nm
Battery	Bosch 500Wh
Display	Bosch Intuvia
Rear hub, internal gear	Enviolo Cargo, 36H
Shifter	Enviolo TR - Trekking
Drive line	Chain, KMC X1 Silver 102L
Rear sprocket	Enviolo 17T flat
Front sprocket	Lasco 38T, 4 hole, 104BCD
Chainguard	Hebie chainglider front 38T, 350R NV16, 16-22T for Enviolo
Rear brake	Tektro Dorado HD-E730, Lever Right, 2300mm hose
Brake rotor rear	Tektro TR-203-17, 203mm 2.3mm
Adapter rear	Tektro A12, PM180-PM203
Front brake	Tektro Dorado HD-E730, Lever Left, 2000mm hose
Brake rotor front	Tektro TR-180-17, 180mm 2.3mm
Adapter front	Tektro A3, IS-PM180
Brake pads	Metallic Ceramic (Red) D40.11
Rear light	Spanninga Plateo XE 6V-36V
Front light	Lezyne Mini E65, 980mm cable
Front fork	UA rigid fork
Steering rod	UA Shorty steering rod & linkage
Stem	TranzX JD-ST17-2 black 1-1/8 25,4 110mm
Handlebar	Ergotec Moon cruiser 25,4 black
Grips	Ergon GC10
Pedals	C558
Seatpost	Satori Trident 31,6 400mm Black
Saddle	Selle Royal Rio Plus
Cranks	Lasco EB05 BNI 170mm
Rear rim	Ryde Andra 40 Double wall 26" x 1.75; Sapim spokes (13G)
Front rim	Ryde Andra 40 Double wall 20" x 1.75; Sapim spokes (14G)
Front hub	Shimano HB-M525A, 36H
Rear tire	Schwalbe Big Ben Plus 55-559
Front tire	Schwalbe Big Ben Plus 55-406
Valve	Schrader
Rear fender	SKS 65mm 26" Black matte
Front fender	SKS 65mm 20" Black matte
Frame colour	Black or White
Weight bike	46Kg
Outer dimensions	L 203cm x W 70cm x H 110cm
Max total weight	190Kg Bike + rider + load
Max front load	50Kg
Max rider weight	125Kg
Max rear load	25Kg

* As Urban Arrow works to continuously improve its products all specifications are subject to change. Hence, no rights can be derived from this publication. Last updated 01-03-2021



URBAN ARROW SHORTY

Specification Sheet - EN

Bosch Cargo Line | 500Wh | Magura*

SPECIFICATIONS

Frame (rear)	UA4.2, aluminium
Motor	Bosch Cargo Line Gen 4, 250W - max. 85 Nm
Battery	Bosch 500Wh
Display	Bosch Intuvia
Rear hub, internal gear	Enviolo Cargo, 36H
Shifter	Enviolo TR - Trekking
Drive line	Chain, KMC X1 Silver 100L
Rear sprocket	Enviolo 17T flat
Front sprocket	Miranda 38T Chainflow, 104BCD
Chainguard	Hebie chainglider front 38T, 350R NV16, 16-22T for Enviolo
Rear brake	Magura Cme Lever right w banjo, 2200mm hose
Brake rotor rear	Magura MDR-C 203mm
Adapter rear	Magura QM44 PM180-PM203
Front brake	Magura Cme Lever Left w banjo, 1900mm hose
Brake rotor front	Magura MDR-C 180mm
Adapter front	Magura QM12 IS-PM180
Brake pads	8.S pads
Rear light	Spanninga Plateo XE 6V-36V
Front light	Lezyne Power E115, 980mm cable
Front fork	UA rigid fork
Steering rod	UA Shorty steering rod & linkage
Stem	TranzX JD-ST17-2 black 1-1/8 25,4 110mm
Handlebar	Ergotec Moon cruiser 25,4 black
Grips	Ergon GC10
Pedals	C558
Seatpost	Satori Trident 31,6 400mm Black
Saddle	Selle Royal Rio Plus
Cranks	Miranda Delta 0 , ISIS
Rear rim	Ryde Andra 40 Double wall 26" x 1.75; Sapim spokes (13G)
Front rim	Ryde Andra 40 Double wall 20" x 1.75; Sapim spokes (14G)
Front hub	Shimano HB-M525A, 36H
Rear tire	Schwalbe Big Ben Plus 55-559
Front tire	Schwalbe Big Ben Plus 55-406
Valve	Schrader
Rear fender	SKS 65mm 26" Black matte
Front fender	SKS 65mm 20" Black matte
Frame colour	Black or White
Weight bike	46Kg
Outer dimensions	L 203cm x W 70cm x H 110cm
Max total weight	190Kg Bike + rider + load
Max front load	50Kg
Max rider weight	125Kg
Max rear load	25Kg

* As Urban Arrow works to continuously improve its products all specifications are subject to change. Hence, no rights can be derived from this publication. **Last updated 01-03-2021**